

# Wykaz elementów

<b>Rusztowanie aluminiowe 4100-S z poręczą Safe-Quick</b>								
<b>0.75 x 1.85 m</b>								
Wysokość ostatniego podestu (m)		2.20 m	3.20 m	4.20 m	5.20 m	6.20 m <sup>1)</sup>	7.20 m	8.20 m <sup>1)</sup>
Wysokość robocza (m)		4.20 m	5.20 m	6.20 m	7.20 m	8.20 m	9.20 m	10.20 m
nr katalogowy		<b>C410009</b>	<b>C415005</b>	<b>C410010</b>	<b>C415006</b>	<b>C410011</b>	<b>C415007</b>	<b>C410012</b>
<b>Wykaz elementów</b>	<b>Nr.ele.</b>							
Rama 0,75 x 2,0 m	303470	2	4	4	6	6	8	8
Rama 0,75 x 1,0 m	303440	2		2		2		2
Koło jezdne Ø 200 mm	511220	4	4	4	4	4	4	4
Pomost 1,85 m z klapą	305010	1	2	2	2	2	3	3
Poręcz podwójna 1,85 m Safe-Quick	360270	2	3	4	5	6	7	8
Stężenie ukośne 1,85 m	304321	2	1	2	1	2	1	2
Stężenie poziome 1,85 m	304304	2	2	2	2	2	2	2
Stabilizator	305662		4	4	4	4	4	4
Komplet burt 0,75 x 1,85 m	305565	1	1	1	1	1	1	1

<b>Rusztowanie aluminiowe 4100-S z poręczą Safe-Quick</b>								
<b>0.75 x 2.45 m</b>								
Wysokość ostatniego podestu (m)		2.20 m	3.20 m	4.20 m	5.20 m	6.20 m <sup>1)</sup>	7.20 m	8.20 m <sup>1)</sup>
Wysokość robocza (m)		4.20 m	5.20 m	6.20 m	7.20 m	8.20 m	9.20 m	10.20 m
nr katalogowy		<b>C410013</b>	<b>C415008</b>	<b>C410014</b>	<b>C415009</b>	<b>C410015</b>	<b>C415010</b>	<b>C410016</b>
<b>Wykaz elementów</b>	<b>Nr.ele.</b>							
Rama 0,75 x 2,0 m	303470	2	4	4	6	6	8	8
Rama 0,75 x 1,0 m	303440	2		2		2		2
Koło jezdne Ø 200 mm	511220	4	4	4	4	4	4	4
Pomost 2,45 m z klapą	305110	1	2	2	2	2	3	3
Poręcz podwójna 2,45 m Safe-Quick	360271	2	3	4	5	6	7	8
Stężenie ukośne 2,45 m	304316	2	1	2	1	2	1	2
Stężenie poziome 2,45 m	304306	2	2	2	2	2	2	2
Stabilizator	305662		4	4	4	4	4	4
Komplet burt 0,75 x 2,45 m	305570	1	1	1	1	1	1	1