

Wykaz elementów

Rusztowanie aluminiowe 4200-S z poręczą Safe-Quick

1.35 x 1.85 m

Wysokość ostatniego podestu (m)	2.20 m	3.20 m	4.20 m	5.20 m	6.20 m ¹⁾	7.20 m	8.20 m ¹⁾	9.20 m	10.20 m ¹⁾	11.20 m	12.20 m ¹⁾
Wysokość robocza (m)	4.20 m	5.20 m	6.20 m	7.20 m	8.20 m	9.20 m	10.20 m	11.20 m	12.20 m	13.20 m	14.20 m
nr katalogowy	C420013	C425007	C420014	C425008	C420015	C425009	C420016	C425010	C420017	C425011	C420018
Wykaz elementów	Nr.ele.										
Rama 1,35 x 2,0 m	2	4	4	6	6	8	8	10	10	12	12
Rama 1,35 x 1,0 m	2		2		2		2		2		2
Koło jezdne Ø 200 mm	4	4	4	4	4	4	4	4	4	4	4
Pomost 1,85 m z klapą	1	1	2	2	2	3	3	4	4	5	5
Pomost 1,85 m bez kłapy	1	2	1	1	1	1	1	1	1	1	1
Poręcz podwójna 1,85 m Safe-Quick	2	2	4	4	6	6	8	8	10	10	12
Stężenie ukośne 1,85 m	4	4	4	4	4	4	4	4	4	4	4
Stężenie poziome 1,85 m	2	2	2	2	2	2	2	2	2	2	2
Stabilizator		4	4	4	4	4	4	4	4	4	4
Komplet burt 1,35 x 1,85 m	1	1	1	1	1	1	1	1	1	1	1

Rusztowanie aluminiowe 4200-S z poręczą Safe-Quick

1.35 x 2.45 m

Wysokość ostatniego podestu (m)	2.20 m	3.20 m	4.20 m	5.20 m	6.20 m ¹⁾	7.20 m	8.20 m ¹⁾	9.20 m	10.20 m ¹⁾	11.20 m	12.20 m ¹⁾
Wysokość robocza (m)	4.20 m	5.20 m	6.20 m	7.20 m	8.20 m	9.20 m	10.20 m	11.20 m	12.20 m	13.20 m	14.20 m
nr katalogowy	C420019	C425012	C420020	C425013	C420021	C425014	C420022	C425015	C420023	C425016	C420024
Wykaz elementów	Nr.ele.										
Rama 1,35 x 2,0 m	2	4	4	6	6	8	8	10	10	12	12
Rama 1,35 x 1,0 m	2		2		2		2		2		2
Koło jezdne Ø 200 mm	4	4	4	4	4	4	4	4	4	4	4
Pomost 2,45 m z klapą	1	1	2	2	2	3	3	4	4	5	5
Pomost 2,45 m bez kłapy	1	2	1	1	1	1	1	1	1	1	1
Poręcz podwójna 2,45 m Safe-Quick	2	2	4	4	6	6	8	8	10	10	12
Stężenie ukośne 2,45 m	4	4	4	4	4	4	4	4	4	4	4
Stężenie poziome 2,45 m	2	2	2	2	2	2	2	2	2	2	2
Stabilizator		4	4	4	4	4	4	4	4	4	4
Komplet burt 1,35 x 2,45 m	1	1	1	1	1	1	1	1	1	1	1